

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Previously presented) A light source driving circuit comprising:
 - a light source section;
 - a charging section;
 - a power supply section including a constant-current circuit for charging said charging section via said constant-current circuit;
 - a switching section for connecting said charging section to said power supply section or to said light source section; and
 - a control section for controlling said switching section so as to connect said charging section to said power supply section, thereby charging said charging section, and so as to disconnect said charging section from said power supply section and connect said charging section to said light source section, thereby causing said light source section to emit light.
2. (Original) The light source driving circuit according to claim 1, wherein a non-emitting period, which includes a period during which said charging section is connected to said power supply section for charging, is set longer than an emitting period during which said light source section is caused to emit light.
3. (Original) The light source driving circuit according to claim 1,

wherein said switching section includes a first switch and a second switch,
and

wherein said power supply section is connected to said charging section
via said first switch, and said light source section is connected to
said charging section via said second switch.

4. (Original) The light source driving circuit according to claim 3,
wherein said first switch and said second switch each have a control
terminal, and
wherein said first switch and said second switch are controlled so as to
conduct cyclically and in an alternating drive by a control signal that
said control section applies to said each control terminal.
5. (Cancelled).
6. (Previously presented) The light source driving circuit according to claim 1,
wherein said charging section includes a driving capacitor.
7. (Previously presented) The light source driving circuit according to claim 1,
wherein said light source section includes a light-emitting diode.
8. (Original) The light source driving circuit according to claim 1,
wherein said light source section includes a first light source for emitting
first color light, a second light source for emitting second color light,
and a third light source for emitting third color light.

9. (Original) The light source driving circuit according to claim 8,
wherein said switching section includes a first switch, a second switch, a third switch, and a fourth switch, and
wherein said power supply section is connected to said charging section via said first switch, said first light source is connected to said charging section via said second switch, said second light source is connected to said charging section via said third switch, and said third light source is connected to said charging section via said fourth switch.
10. (Original) The light source driving circuit according to claim 9,
wherein said first switch, said second switch, said third switch, and said fourth switch each have a control terminal, and
wherein said first switch, said second switch, said third switch, and said fourth switch are controlled so as to conduct cyclically and in an alternating drive by a control signal that said control section applies to said each control terminal.
11. (Original) The light source driving circuit according to claim 10,
wherein said power supply section includes a constant-current circuit, and
wherein said power supply section charges said charging section via said constant-current circuit.
12. (Original) The light source driving circuit according to claim 1,
wherein said light source section includes a first light source for emitting first color light, a second light source for emitting second color light, and a third light source for emitting third color light, and

said charging section includes a first driving capacitor corresponding to said first light source, a second driving capacitor corresponding to said second light source, and a third driving capacitor corresponding to said third light source.

13. (Currently amended) The light source driving circuit according to claim 12, wherein said switching section includes a first switch, a second switch, a third switch, a fourth switch, a fifth switch, and a sixth switch, and wherein said power supply section is connected to said first driving capacitor via said first switch, said power supply section is connected to said second driving capacitor via said second switch, said power supply section is connected to said third driving capacitor via said third switch, said first light source is connected to said first driving capacitor via said fourth switch, said second light source is connected to said second driving capacitor via said fifth switch, and said third light source is connected to said third driving capacitor via said sixth switch.

14. (Original) The light source driving circuit according to claim 13, wherein said first switch, said second switch, said third switch, said fourth switch, said fifth switch, and said sixth switch each have a control terminal, and wherein said first switch, said second switch, said third switch, said fourth switch, said fifth switch, and said sixth switch are controlled so as to conduct cyclically and in an alternating drive by a control signal that said control section applies to said each control terminal.

15. (Original) The light source driving circuit according to claim 14,

wherein said power supply section includes a constant-current circuit, and

wherein said power supply section charges said first driving capacitor,
said second driving capacitor, and said third driving capacitor via
said constant-current circuit.

16. (Original) A lighting apparatus which uses a light source driving circuit according to claim 8.
17. (Original) A display apparatus which uses a light source driving circuit according to claim 8.
18. (Original) A field sequential color liquid crystal display apparatus which uses a light source driving circuit according to claim 8.
19. (Original) An information appliance which uses a light source driving circuit according to claim 8.